

NetBackup™ for KVM Administrator's Guide

Release 11.2.0.1

Last updated: 2026-09-07

Legal Notice

Copyright © 2026 Cohesity, Inc. All rights reserved.

© 2026 Cohesity, Inc. All Rights Reserved. Cohesity, the Cohesity Logo and other Cohesity Marks are trademarks of Cohesity, Inc. in the US and/or internationally. The information supplied herein is the confidential and proprietary information of Cohesity and may only be used (a) by the intended recipients and (b) in conjunction with validly licensed Cohesity software and services. Find the terms of Cohesity licenses at www.cohesity.com/agreements.

THE DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID. COHESITY SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS DOCUMENTATION. THE INFORMATION CONTAINED IN THIS DOCUMENTATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

Cohesity Support

Reach Cohesity Support

There are several ways to create a Cohesity support case.

- Go to [Cohesity Support](#), to search in our knowledge base; or contact us by phone - United States and Canada: 1-855-9CO-HESI (926-4374), option 2.
- Log in to the [Cohesity Support Portal](#) to create a new case.
- Click the (?) icon on the Cohesity UI and select Support Portal.

Support/Service Assistance

First, contact the Service Provider that you have contracted for service and support. If you work directly with Cohesity and have a product warranty/entitlement, repair pricing, or technical support-related question, see your options below:

- To find solutions to your product issues or for suggestions or best practices, visit the [Cohesity Knowledge Base](#).
- Log in to the [Cohesity Support Portal](#) to create a new case.
- To monitor your open cases, log in to the portal and click the **Cases** tab on the home page. This page should have all the case statuses and updates. You can also view individual case status.

Cohesity Software Running on Partner Hardware

For Cohesity software running on qualified third-party hardware, the following support workflow applies:

1. The customer may contact Cohesity Support first if the issue cannot be determined as a hardware issue.

Note: Cohesity cannot process hardware replacement requests for partner hardware.

2. Cohesity Support triages the issue. If it is a software issue, Cohesity Support continues to work on it.
3. If it is a hardware/firmware issue or is suspected to be a hardware/firmware issue, Cohesity provides information about the issue to the customer and requests that the customer open a support ticket with the appropriate partner.
4. If needed, Cohesity Support can join a three-way call with the partner and the customer.
5. The customer informs Cohesity Support on the progress of the partner's case.

Contents

Chapter 1	Introduction	6
	About NetBackup for KVM	6
	Supported configurations for OLVM backup and restore	7
Chapter 2	Installation and configuration overview	9
	Planning the installation for NetBackup for KVM	9
	Verifying the operating system and platform compatibility	9
	NetBackup server and client requirements	10
	NetBackup configuration overview	11
Chapter 3	Managing KVM hosts	12
	Add KVM hosts	12
	Add an OLVM server	13
	About KVM discovery	14
	Change the autodiscovery frequency of KVM assets	15
	Discover KVM host assets manually	15
	Browse KVM assets	15
	Validate a KVM host	16
	Remove a KVM host	17
	Disable a KVM host	17
	Change resource limits for KVM resource types	18
Chapter 4	Configuring RBAC roles for KVM administrators	20
	RBAC roles for the KVM administrator	20
	Assigning permissions at specific KVM object levels	20
Chapter 5	Protecting KVM virtual machines	22
	About configuring a backup policy for KVM	22
	Limitations for KVM backups	23
	Configure an OLVM backup policy	23
	Limitations for OLVM backups	25
	About automatic virtual machine selection	26

Add a policy for KVM	26
About policy attributes	27
Schedule properties	28
Add KVM hosts to a policy	29
Configure a query to select KVM virtual machines for backup	29
Query builder reference for KVM virtual machines	31
Use Advanced mode to create a query for virtual machine selection	34
Example queries to select VMs for backup	35
Test a VM query	35
About the Reuse VM selection query results option	36
Backup options on the KVM attributes tab	37
KVM Backup Host	37
Optimizations options (KVM)	38
Primary VM identifier options (KVM)	39
NetBackup character restrictions for the Primary VM identifier	39
Existing snapshot handling options (KVM)	41
KVM - Advanced attributes	42
View the protection status of KVM virtual machines	42
Perform a manual backup	43

Chapter 6 Recovering KVM virtual machines 44

Considerations and limitations for KVM recovery	44
About the pre-recovery check	45
Recover a KVM virtual machine	45
Download files and folders	47
Single-file restore (SFR) to a NetBackup client	48
Restore OLVM Virtual Machines	49
Restore files from OLVM VM backups (Single file restore)	50

Chapter 7 Troubleshooting KVM backups and recovery 51

NetBackup logging for KVM	51
Configuring VxMS logging	53
Troubleshooting a KVM discovery or a validate operation	55
Using a custom overlay path location	56
Troubleshooting OLVM backup and restore	56
OLVM Backup Performance Tuning (bp.conf)	58

Introduction

This chapter includes the following topics:

- [About NetBackup for KVM](#)
- [Supported configurations for OLVM backup and restore](#)

About NetBackup for KVM

NetBackup for KVM provides backup and restore of the KVM virtual machines that run on KVM hosts and OLVM virtual machines that run on OLVM servers. This workload provides the following capabilities:

For KVM

- Automatically creates consistent (quiesced) backups.
- Performs full and incremental backups of guest virtual machines on KVM hosts..
- Backs up the virtual machines that are either powered on or powered off.
- Can recover backups to the original KVM host or a different KVM host.
- Can restore virtual machines from the backup.
- Performs backups directly from the KVM hosts. No additional management application layer (for example, oVirt) is required.
- Supports the following disk formats: QCOW2, raw-formatted disks, and block device disks.
- Can perform Single-File-Restore (SFR) operations on the KVM host. Specify the policy type as **KVM** on the **Recovery > Regular recovery** web UI screen.
- Supports Accelerator
- Supports Hypervisor credentials

In this guide, a KVM "domain" is referred to as virtual machine or VM.

For OLVM:

- Perform full and incremental Changed Block Tracking (CBT) backups of OLVM VMs. Backups are crash-consistent.
- Run Accelerator / Incremental-Forever backups. CBT state is preserved when a VM is live-migrated to a different OLVM host which means that the next incremental backup does not reset to a full backup.
- Restore a full VM to OLVM. The restored VM includes all original disks, NIC configuration, BIOS/firmware type, high-availability configuration, VM tags, boot order, and delete protection. No manual post-restore steps are required.
- Restore individual files from a VM backup, either to a NetBackup client inside the guest VM or by downloading files directly from the NetBackup Web UI.
- Use Intelligent Policies to automatically include VMs.
- Integrate OLVM backups with Storage Lifecycle Policies (SLP) and Automatic Image Replication (AIR).
- Back up VMs on NFS, Fiber Channel (FC), and iSCSI storage domains.
- Manage all OLVM backup and restore operations from the NetBackup Web UI.

Supported configurations for OLVM backup and restore

Existing generic KVM policies continue to work and are not affected by OLVM support. You can protect traditional KVM and OLVM VMs using KVM policies in the same NetBackup domain.

If you currently use the RHV policy type to protect an OLVM environment, those policies continue to function. To use the native OLVM capabilities (CBT survival across live migration, management-layer-aware restore, no agent on hypervisor hosts), create new KVM policies with OLVM selected as the management server type. RHV policies do not gain OLVM management-layer awareness. There is no separate OLVM policy type.

Table 1-1

Component	Requirement	Notes
NetBackup version	11.2.0.1 or later	Required on both the NetBackup primary server and the backup host. Older NetBackup versions do not include OLVM support.

Table 1-1 *(continued)*

Component	Requirement	Notes
OLVM version	4.5 or later	OLVM 4.5 is Oracle's current lifecycle ("N") release. Earlier OLVM versions are not supported.
oVirt API	oVirt REST API v4	Required for VM discovery, backup, and restore operations.
Backup Host	NetBackup media server or NetBackup client	The Backup Host communicates with the OLVM engine and handles all disk data transfers. No agent is required on OLVM hypervisor hosts.
Storage domain types	NFS, Fiber Channel (FC), iSCSI	All three storage domain types are supported. The Backup Host must have network access to the applicable storage.
Guest agent (SFR to client)	NetBackup client in the guest VM	Required only for agent-based single-file restore. Not required for full VM backup/restore or Web UI file download.

Installation and configuration overview

This chapter includes the following topics:

- [Planning the installation for NetBackup for KVM](#)
- [NetBackup configuration overview](#)

Planning the installation for NetBackup for KVM

Table 2-1 Installation steps for NetBackup for KVM

Step	Action	Description
Step 1	Verify the operating system and platform compatibility.	See “Verifying the operating system and platform compatibility” on page 9.
Step 2	For unmanaged KVM hosts, verify that a supported version of libvirt is installed on each KVM host.	See “Verifying the operating system and platform compatibility” on page 9.
Step 3	For unmanaged KVM hosts, install the NetBackup client software on the KVM hosts that have the virtual machines that you want to back up.	See “NetBackup server and client requirements” on page 10.

Verifying the operating system and platform compatibility

Verify that the NetBackup for KVM agent is supported on your operating system or platform.

To verify operating system and compatibility

- 1 Go to the NetBackup compatibility list site.
<https://support.cohesity.com/s/article/article-100040093>
- 2 For information on the supported KVM versions and support versions of libvirt, select the link for following document:
[NetBackup Software Compatibility List](#)

NetBackup server and client requirements

Before you install NetBackup, review the requirements for the NetBackup server and the NetBackup clients.

NetBackup server requirements

Verify that the following requirements are met for the NetBackup server:

- The NetBackup server software is installed and operational on the NetBackup server.
 See the [NetBackup Installation Guide](#).
- Make sure that you configure any backup media that the storage unit uses. The number of media volumes that are required depends on several things:
 - The devices that are used and the storage capacity of the media.
 - The sizes of the databases that you want to back up.
 - The amount of data that you want to archive.
 - The size of your backups.
 - The frequency of backups or archives.
 - The length of retention of the backup images.
 See the [NetBackup Administrator's Guide, Volume I](#).

NetBackup client requirements

Verify that the following requirements are met for the NetBackup clients:

For unmanaged KVM hosts:

- The client software is installed on each KVM host. Also verify that a supported version of libvirt is installed on each KVM host.
- To use the new features that are included in NetBackup for KVM in NetBackup 11.2.0.1, you must upgrade your NetBackup for KVM clients to NetBackup 11.2.0.1. The NetBackup media server must use the same version as the NetBackup for KVM client or a higher version than the client.

NetBackup configuration overview

After the installation of NetBackup, continue with the following configuration tasks.

Table 2-2 NetBackup configuration tasks

Sequence	Tasks
Phase 1	Add the KVM hosts. You must complete the discovery of KVM assets before you configure any RBAC roles for this workload. See “Add KVM hosts” on page 12.
Phase 2	Configure the NetBackup RBAC roles for KVM administrators. Contact your NetBackup administrator for assistance. See “RBAC roles for the KVM administrator” on page 20.
Phase 3	Create a NetBackup policy for KVM. See “Add a policy for KVM” on page 26.
Phase 4	Perform a backup. See “Perform a manual backup” on page 43.

Managing KVM hosts

This chapter includes the following topics:

- [Add KVM hosts](#)
- [Add an OLVM server](#)
- [About KVM discovery](#)
- [Browse KVM assets](#)
- [Validate a KVM host](#)
- [Remove a KVM host](#)
- [Disable a KVM host](#)
- [Change resource limits for KVM resource types](#)

Add KVM hosts

To discover virtual machines in the KVM environment you must first add the KVM hosts to NetBackup.

To add a KVM host

- 1 On the left, select **Workloads > KVM**, then select the **Hosts** tab.
- 2 In the right pane, select **Add**.
NetBackup displays the Linux hosts where the NetBackup client is installed.
- 3 In the **Platform** field, select **KVM (libvirt / QEMU)**.
- 4 In the **Machine** field, select the host from the list.
- 5 Specify the credentials that you need to connect to the underlying Hypervisor on the KVM host.

Select one of the following the credential types:

- Default - Select the default credential option and click **Add**.
NetBackup validates the KVM host and registers it.
- Custom - Select the custom credential option to see the following options:
 - Select existing credential
 - Add a new credential

On the credentials UI page, specify the required credentials or add new credentials and save the information.

Add an OLVM server

Register your OLVM server with NetBackup so that NetBackup can discover and protect your OLVM VMs. You can register an OLVM server by providing the engine host name and credentials on the KVM Hosts page in the NetBackup Web UI. OLVM servers are listed and managed alongside traditional KVM hosts under a single unified view.

You can register multiple OLVM servers in a single NetBackup domain.

Prerequisites:

- Verify that your OLVM environment is running version 4.5 or later.
- Verify that the NetBackup Backup Host has network access to the OLVM engine (HTTPS, port 443) and to the OLVM ImageIO daemon on each hypervisor host (HTTPS).
- Obtain the OLVM engine host name and an account with sufficient privileges to discover VMs, create backups, and initiate restores. Refer to your OLVM documentation for required permissions.
- Verify that your NetBackup primary server and backup host are running release 11.2.0.1 or later.
- Verify that the ovirt-imageio service is running on every OLVM host that stores backed-up disks.
- Verify TLS trust is configured between the Backup Host and the OLVM engine and hosts.
- Port 54322 is required for incremental (CBT) backups. If only the engine proxy port (54323) is reachable, backups continue to run, but the full disk data is transferred during each backup.
- Verify the OLVM account has sufficient privileges: inventory read, backup and checkpoint create/finalize, snapshot, and image transfer. For restores, the

account also needs the following permissions: VM and disk create/delete, NIC and tag attach, HA settings, image-transfer upload, and placement into the target cluster.

To add an OLVM server

- 1 On the left, select **Workloads > KVM**, then select the **Hosts** tab.
- 2 In the right pane, select **Add**.
- 3 In the **Platform** field, select **OLVM (Oracle Linux Virtualization Manager)**.
- 4 In the **Hostname** field, enter the host name of the OLVM engine (oVirt Manager). For example: olvm-engine.example.com
- 5 In the **Port** field, enter the OLVM engine port. If not specified, the default port (443) is used.
- 6 In the **Validation backup host** field, select the NetBackup media server/client used to communicate with the OLVM server.
- 7 Specify the credentials that you need to connect to the OLVM server.

Select the **Custom credential** type to see the following options:

- Select existing credential
 - Add a new credential
- On the **Credentials** page, specify the required credentials or add new credentials and save the information.

Note: Enter the OLVM account username in the format user@domain (for example, admin@internal). Authentication fails if the @domain suffix is omitted.

About KVM discovery

NetBackup automatically starts the discovery of the KVM virtual machines when you add a KVM host or an OLVM server to NetBackup. Autodiscovery also occurs at set intervals. (The default interval is every 8 hours.)

You can change the autodiscovery frequency.

See [“Change the autodiscovery frequency of KVM assets”](#) on page 15.

To discover the VMs immediately, see the following topic:

See [“Discover KVM host assets manually”](#) on page 15.

Change the autodiscovery frequency of KVM assets

Automatic discovery of KVM and OLVM virtual machines occurs at regular intervals. The default frequency is every 8 hours. Use this procedure to change the autodiscovery frequency.

To change the frequency of autodiscovery of KVM and OLVM assets

- 1 On the left, select **Workloads > KVM**.
- 2 At the top right, select **KVM settings > Autodiscovery**.
- 3 Locate the **Frequency** setting and select **Edit**.
- 4 Type the value or use the up and down arrows to choose the frequency value.

The range from which you can choose is 1 hour to 24 hours. To set the autodiscovery frequency in minutes or seconds or to disable autodiscovery, you must use the KVM autodiscovery API.
- 5 Select **Save**.

Discover KVM host assets manually

You can manually start the NetBackup discovery process if you want to immediately discover new KVM and OLVM virtual machines in your environment.

To discover new KVM and OLVM virtual machines

- 1 On the left, select **Workloads > KVM**.
- 2 Select the **Hosts** tab.
- 3 Select the checkbox for each host that contains the virtual machines that you want to discover.
- 4 Select **Discover**.

Browse KVM assets

You can browse KVM and OLVM virtual machines to view their details such as how they are protected and recovery points that are available. You can browse KVM hosts and OLVM servers to see discovery information for those hosts.

Browse KVM virtual machines

On the **Virtual machines** tab you can view and manage virtual machines, including how they are protected.

To browse KVM and OLVM virtual machines

- 1 On the left, select **Workloads > KVM**.
- 2 Select the **Virtual machines** tab.
- 3 To view the available actions for a virtual machine, select the check box for the virtual machine.
- 4 To view the details for a virtual machine, select the link for the virtual machine. You can perform the following tasks.
 - To see the available recovery points for the virtual machine, select **Recovery points**.
 - To view the restore jobs for the virtual machine, select **Restore activity**.
 - To view the roles that have access to the virtual machine, select the **Permissions** tab.

Browse KVM hosts

On the **Hosts** tab you can view and manage KVM hosts and OLVM servers.

To browse KVM hosts and OLVM servers

- 1 On the left, select **Workloads > KVM**.
- 2 Select the **Hosts** tab.

You can view their discovery status, the last discovery attempt, the validation status of each host, and when each host was last validated.
- 3 To view the available actions for hosts, select the check box for each host.

Validate a KVM host

You can validate a KVM host or OLVM server to verify that NetBackup can connect to it. For a KVM (libvirt) host, validation verifies that NetBackup can connect to the host and that a supported libvirt version is installed. For an OLVM server, validation verifies that NetBackup can connect to the oVirt engine and that the engine meets the minimum supported version requirements.

- The KVM host or OLVM server was disconnected (for example, for maintenance).
- The NetBackup server or client software was upgraded on the KVM host.
- A new libvirt version was installed on the KVM host.

To validate a KVM host or OLVM server

- 1 On the left, select **Workloads > KVM**, then select the **Hosts** tab.
- 2 In the right pane, locate the KVM host or OLVM server.
- 3 Select **Actions > Validate**.

Remove a KVM host

If you no longer need to protect a KVM host or OLVM server, you can remove it from the list of registered KVM hosts.

Note the following:

- VMs continue to display in NetBackup until all the existing images have expired and 30 days have passed since the last discovery.
- The KVM host still exists as a client in NetBackup until you uninstall the NetBackup server or client software from the KVM host.

To remove a KVM host or OLVM server

- 1 On the left, select **Workloads > KVM**, then select the **Hosts** tab.
- 2 In the right pane, locate the KVM host or OLVM server.
- 3 Select **Actions > Remove**.
- 4 Remove the KVM host or OLVM server from any NetBackup policies.

Disable a KVM host

You can disable a KVM host or OLVM server in certain situations, such as if the host is offline for maintenance or for other reasons. Only registered KVM hosts and OLVM servers can be disabled.

Backup jobs will fail with error 1027 for the disabled KVM hosts and OLVM servers.

To disable a KVM host or OLVM server

- 1 On the left, select **Workloads > KVM**, then select the **Hosts** tab.
- 2 Select the host that you want to disable and click **Disable**.

You can enable the disabled hosts to resume backup jobs for the virtual machines from the KVM hosts and OLVM servers.

Change resource limits for KVM resource types

KVM resource limits control the number of backups that can be performed simultaneously on a KVM host or OLVM server. The settings apply to all NetBackup policies for the primary server that you selected.

For example, to avoid overloading the KVM host or OLVM server, you can place a limit on the number of concurrent backup jobs per KVM host or OLVM server, with the setting **Backup Jobs per KVM Host**.

To change the resource limits for KVM resource types

- 1 Review the limitations for resource limits.

See [the section called “Limitations on global limits for KVM resources”](#) on page 19.

- 2 On the left, select **Workloads > KVM**.

- 3 On the top right, select **KVM settings > Resource limits**.

For each resource, the default value is **0** (No limit).

Limits indicates the number of simultaneous backups that can be performed for the KVM host(s) or OLVM servers. This value is the global limit. The **Override** value indicates how many KVM hosts or OLVM servers have any limits that are different from the global limit.

- 4 To change the limit for the resource **Backup Jobs per KVM Host**, select **Edit**.

- 5 Choose from the following options.

Set a global limit for all KVM hosts and OLVM servers.

Locate the **Global** setting and select the **Limits** value that you want to apply.

This value limits the number of simultaneous backups for all KVM hosts and OLVM servers.

Set a limit for a specific KVM host or OLVM server.

Select **Add**.

From the list, enter the name of the KVM host or OLVM server.

Select the **Limits** value that you want to apply.

This value limits the number of simultaneous backups that are performed for the KVM host or OLVM server.

- 6 Select **Save**.

At any point you can select **Reset default values** to remove all the overrides and set all global KVM resource limits to their default values.

Example

The following example illustrates how these limits control simultaneous backups. The settings must be done according to KVM configuration in your environment. Consider a case where a KVM host hosts 20 VMs. When the job runs there are 20 concurrent jobs that start if no resource limit is set, which is default behavior. When the **Backup Jobs per KVM Host** is set to 10, this limit is enforced and 10 backup jobs run concurrently.

Limitations on global limits for KVM resources

The following limitations apply to setting global limits on the use of KVM resources:

- New and changed resource limits may not take effect immediately. It can take a couple of jobs before the resource limit updates are in effect.
- To limit the number of simultaneous jobs per policy, use the **Limit jobs per policy** setting on the policy **Attributes** tab.

Configuring RBAC roles for KVM administrators

This chapter includes the following topics:

- [RBAC roles for the KVM administrator](#)
- [Assigning permissions at specific KVM object levels](#)

RBAC roles for the KVM administrator

NetBackup enables control over which users can access which KVM resources using Role Based Access Control (RBAC). You can grant RBAC access globally (to all KVM assets) or for specific KVM hosts or individual virtual machines.

The Default KVM Administrator role has access to all KVM assets (global).

Note the following:

- If you choose to create a custom role for KVM assets, permissions can be configured only at the KVM host level or at the KVM virtual machine level.
- To create an RBAC role, you must have the RBAC Administrator role or the permissions to create roles.
- Contact your NetBackup administrator for assistance with creating roles.

Assigning permissions at specific KVM object levels

The RBAC administrator create RBAC roles for KVM that assign permissions to specific KVM objects.

To manage permissions for a KVM host or OLVM server

- 1** On the left, go to **Workloads > KVM**. Then select the **Hosts** tab.
- 2** In the right pane, locate and select the KVM host or OLVM server.
Then select **Manage permissions**.
- 3** Select **Add**.
- 4** Select the role name and the permissions that you want to assign.
- 5** Select **Save**.

To manage permissions for a KVM or OLVM virtual machine

- 1** On the left, go to **Workloads > KVM**. Then select the **Virtual machines** tab.
- 2** Locate and select the virtual machine. Then select **Manage permissions**.
- 3** Select **Add**.
- 4** Select the role name and the permissions that you want to assign.
- 5** Select **Save**.

Protecting KVM virtual machines

This chapter includes the following topics:

- [About configuring a backup policy for KVM](#)
- [Configure an OLVM backup policy](#)
- [About automatic virtual machine selection](#)
- [Add a policy for KVM](#)
- [About policy attributes](#)
- [Schedule properties](#)
- [Add KVM hosts to a policy](#)
- [Configure a query to select KVM virtual machines for backup](#)
- [Backup options on the KVM attributes tab](#)
- [View the protection status of KVM virtual machines](#)
- [Perform a manual backup](#)

About configuring a backup policy for KVM

A backup policy defines the backup criteria for a group of KVM virtual machines.

These criteria include the following:

- Storage unit and media to use
- Policy attributes

- Backup schedules
- The KVM hosts where the virtual machines reside
- KVM backup policies can be used to protect both VMs on KVM hosts and OLVM servers. You can configure a policy to protect only KVM VMs, only OLVM VMs, or a combination of both.
- A query that defines which virtual machines to back up

See [“Add a policy for KVM”](#) on page 26.

Limitations for KVM backups

The following limitations exist for backups of KVM hosts.

- You cannot backup the same KVM virtual machine concurrently.
- The VMs without virtual disks cannot be protected.
- The following QCOW2 image attributes are not supported:
 - Compressed cluster
 - Encrypted disks
- Incremental backups are supported only when BLIB is enabled.
- Changed block tracking (CBT) is supported only for QCOW2 disk types.
 - CBT is supported with QCOW2 v3 or later. Older versions of QCOW2 do not persist the dirty blocks bitmap. Incremental backups of older qcow2 versions back up the full disk.
 - If a QCOW2 disk’s bitmap is in an inconsistent state, incremental backups back up the full disk.
 - The dirty bitmap tracking should be persistent as long as the QEMU process on the KVM host is not terminated. If this process is shut down, incremental backups back up the full disk.
 - Changed blocks are not captured for raw and block device disk types. Incremental backups of these disk types back up the full disk.
- Manual snapshot / checkpoint manipulation outside of NetBackup can break incremental chains.

Configure an OLVM backup policy

You can create a KVM backup policy for your OLVM VMs. There is no separate OLVM policy type. OLVM VM backups run as KVM policies. KVM policies support

full backups, incremental backups (differential or cumulative) using Changed Block Tracking (CBT), and the Accelerator policy option.

To configure an OLVM backup policy

- 1 In the NetBackup Web UI, navigate to **Policies** and click **Add**.
- 2 On the **Attributes** tab, set **Policy type** to **KVM**.
- 3 (Optional) Select a **Policy storage** or **Storage Lifecycle Policy (SLP)** for backup image management
- 4 On the **Schedules** tab, add one or more schedules. The following schedule types are available for KVM policies:

Schedule type	Backup mode	Description
Full backup	Full	Backs up all blocks on each VM disk. Used to establish an initial baseline or on a periodic schedule.
Differential incremental backup	Incremental (CBT)	Backs up only the blocks that changed since the last backup (full or incremental). Uses oVirt Changed Block Tracking (CBT). CBT state is preserved when a VM is live-migrated to a different OLVM host.
Cumulative incremental backup	Incremental (CBT)	Backs up all blocks that changed since the last full backup. Uses oVirt Changed Block Tracking (CBT). CBT state is preserved when a VM is live-migrated to a different OLVM host.

Note: Accelerator is a policy option on the Attributes tab. Enable it alongside a differential, cumulative incremental, or full backup schedule to skip data already known from the previous backup, using the same checkpoint chain as CBT.

- 5 On the **KVM hosts** tab, select the OLVM server you registered.
- 6 On the **Backup selections** tab, add the VMs to protect using an Intelligent Policy. KVM policies do not support adding VMs manually. Create a query that dynamically selects the virtual machines.

See [“Configure a query to select KVM virtual machines for backup”](#) on page 29.

- 7 Select the **KVM attributes** tab to set OLVM related options.
See [“Backup options on the KVM attributes tab”](#) on page 37.
- 8 Click **OK** to save the policy.

Limitations for OLVM backups

- Upstream (non-Oracle) oVirt is not validated. Only Oracle OLVM is supported.
- There is no per-tenant OLVM concurrency quota. Concurrency is bounded by existing NetBackup global controls.
- The asynchronous transfer buffer pool is allocated per job and is not shared across concurrent jobs.
- Supported storage domain types are NFS, Fibre Channel (FC), and iSCSI.
- Incrementals will back up full disk data for read-only disks.
- Backup of a VM with a read-only disk fails during the snapshot phase when the VM's compatibility version does not enable hybrid backup. This failure affects the entire VM backup, not just the read-only disk. Without hybrid backup, OLVM falls back to the libvirt backup API, which does not support including a read-only disk in a backup.

Backups of VMs with read-only disks are supported only when the VM has cluster compatibility version 4.7 or higher (where hybrid backup is enabled).
Recommended action: Raise the cluster's (or the VM's) compatibility version to a level that enables hybrid backup, or clear the disk's read-only attribute if the guest does not require it.

- Backup of a running OLVM VM with a read-only disk can fail, depending on how the disk's incremental backup setting is configured:
 - If **Enable Incremental Backup** is not selected on the read-only disk, a full backup of the VM fails. This happens because NetBackup reads the disk outside the OLVM backup operation, while OLVM has every disk on the VM locked.
 - If **Enable Incremental Backup** is selected and a previous backup has already included the disk, an incremental backup fails. This happens because OLVM requires a changed-block bitmap, and QEMU cannot write a bitmap to a disk the guest holds read-only.

Recommended action: Clear the **Read Only** attribute on the disk attachment, in the OLVM Administration Portal under **Compute > Virtual Machines > virtual machine > Disks**. This is the only option that allows both full and incremental backups to succeed.

If the disk must remain read-only, select **Enable Incremental Backup** on it, and do **one** of the following:

- Protect the virtual machine with full backups only
- Power off the virtual machine before running full or incremental backups.

About automatic virtual machine selection

You can configure NetBackup to automatically select virtual machines based on a range of criteria. You specify the criteria (rules) in the **Query builder** on the NetBackup policy **Backup selections** tab. NetBackup creates a list of the virtual machines that currently meet the rules and adds those virtual machines to the backup.

Automatic selection of virtual machines has the following advantages:

- Simplifies the policy configuration for sites with large virtual environments. You do not need to manually select virtual machines from a long list of hosts: NetBackup selects all the virtual machines that meet the selection rules in the policy's Query builder.
- It allows the backup list to stay up to date with changes in the virtual environment. Eliminates the need to revise the backup list whenever a virtual machine is added or removed.
- Virtual machine selection takes place dynamically at the time of the backup.

Examples of automatic virtual machine selection are the following:

Table 5-1 Examples for automatic virtual machine selection

Example	Description
Limit the backup list to the virtual machines that are currently turned on	If some of your virtual machines are occasionally turned off, NetBackup can be configured to automatically exclude those from the backup list. Among the virtual machines it discovers, NetBackup backs up only the virtual machines that are turned on.
Back up virtual machines based on KVM host	For example, a query rule can select all the virtual machines that reside on a particular KVM host.

Add a policy for KVM

This topic describes how to create a NetBackup policy to back up the KVM virtual machines on one or more KVM hosts.

To add a policy for KVM

- 1 Open the NetBackup web UI.
- 2 On the left, select **Protection > Policies**. Then select **Add**.
- 3 Type a unique name for the new policy.
- 4 From the **Policy type** list, select **KVM**.
- 5 Complete the entries on the **Attributes** tab.
See [“About policy attributes”](#) on page 27.
- 6 Add other policy information as follows:
 - Add schedules.
 - Add the KVM hosts.
See [“Add KVM hosts to a policy”](#) on page 29.
 - Create a query that dynamically selects the virtual machines.
See [“Configure a query to select KVM virtual machines for backup”](#) on page 29.
 - Select the **KVM attributes** tab to set KVM-related options.
See [“Backup options on the KVM attributes tab”](#) on page 37.
- 7 When you have completed the policy configuration, select **Create**.

About policy attributes

With a few exceptions, policy attributes for a KVM policy are managed in the same way as for most other policy types. Certain policy attributes vary according to your specific backup strategy and system configuration.

For more information on policy attributes, see the [NetBackup Administrator's Guide, Volume I](#).

Table 5-2 Policy attributes for NetBackup for KVM policies

Attribute	Description
Policy type	Determines the types of clients that can be backed up with the policy. For KVM virtual machines, select the policy type KVM
Keyword phrase	A textual description of a backup. Useful for browsing backups and restores.

Schedule properties

Table 5-3 Description of schedule properties

Property	Description
Type of backup	Specifies the type of backup that this schedule can control. The selection list shows only the backup types that apply to the policy you want to configure.
Schedule type	You can schedule an automatic backup in one of the following ways: ■ Calendar The Calendar option lets you schedule the backup operations that are based on specific dates, recurring week days, or recurring days of the month. ■ Frequency The Frequency specifies the period of time that can elapse until the next backup operation begins on this schedule. For example, assume that the frequency is 7 days and a successful backup occurs on Wednesday. The next full backup does not occur until the following Wednesday.
Retention	Specifies a retention period to keep backup copies of files before they are deleted. The retention level also denotes a schedule priority within the policy. A higher level has a higher priority. Set the time period to retain at least two full backups of your database. In this way, if one full backup is lost, you have another full backup to restore. For example, if your database is backed up once every Sunday morning, you should select a retention period of at least 2 weeks. The retention period for an application backup schedule refers to the length of time that NetBackup keeps backup images. The retention period for an automatic schedule controls how long NetBackup keeps records of when scheduled backups occurred. For example, if your database is backed up once every Sunday morning, you should select a retention period of at least 2 weeks.
Effect of type of schedule on retention period	The type of schedule you select affects the retention period as follows: ■ Frequency-based scheduling Set a retention period that is longer than the frequency setting for the schedule. For example, if the frequency setting is set to one week, set the retention period to be more than one week. The NetBackup scheduler compares the latest record of the automatic backup schedule to the frequency of that automatic backup schedule. This comparison is done to determine whether a backup is due. So if you set the retention period to expire the record too early, the scheduled backup frequency is unpredictable. However, if you set the retention period to be longer than necessary, the NetBackup catalog accumulates unnecessary records. ■ Calendar-based scheduling The retention period setting is not significant for calendar-based scheduling.

Add KVM hosts to a policy

The KVM hosts list contains the list of the KVM hosts and OLVM servers on which the virtual machines reside that you want to back up. A policy must have at least one KVM host or OLVM server.

For installation requirements, see the following topic.

See [“NetBackup server and client requirements”](#) on page 10.

To add KVM hosts to a policy

- 1 Open the policy and select the **KVM hosts** tab.
- 2 Select **Add**.
- 3 Select the name of the host.
- 4 Select **Select**.

Configure a query to select KVM virtual machines for backup

NetBackup automatically selects KVM virtual machines for backup based on the query criteria that you enter. You specify the criteria (rules) in the Query builder in the policy **Backup selections** tab. You can set up rules to include certain virtual machines for backup, or to exclude virtual machines.

Note: In the NetBackup web UI, you must use OData keywords and OData operators in query rules:

See [“Query builder reference for KVM virtual machines”](#) on page 31.

When the backup job runs, NetBackup creates a list of the virtual machines that currently meet the query rules and backs them up.

To configure the VMs in the backup selections list

- 1 In the policy, select the **Backup selections** tab.

- 2 To create a rule, make selections from the menus.

For the first rule, you can start with the **Field** list, depending on the type of rule. (For the first rule, the only selections available for the field **Join** are blank (none), or NOT.)

Then make a selection for **Operator**.

For the **Value** field: Select the folder icon to browse for values, enter the value manually, or in some cases select a value from the list. The characters you enter manually in the **Value** field must be enclosed in single quotes. Note that browsing for values may take some time in large virtual environments.

See [“Query builder reference for KVM virtual machines”](#) on page 31.

- 3 Select **Add** to add the rule to the **Query** pane.

- 4 Create more rules as needed.

See [“Example queries to select VMs for backup”](#) on page 35.

- 5 To see which virtual machines NetBackup currently selects based on your query, select **Test query**.

The Virtual machines in your current environment that match the rules for selection in the policy are labeled **Included**. Note however that the Test query option does not create the backup list for the policy.

See [“Test a VM query”](#) on page 35.

- 6 To perform an immediate discovery to update the asset information, scroll to the bottom of the **Test query** modal and select **Discover now**.

Note: NetBackup does not run discovery when the KVM policy runs. To reflect any new VMs in the policy, you must manually run discovery to discover those VMs.

- 7 When you are finished reviewing the query results, select **Close**.

- 8 You can specify how long NetBackup uses the latest query results as the backup list for future executions of the policy. Set the time period in **Reuse VM selection query results for**.

See [“About the Reuse VM selection query results option”](#) on page 36.

- 9 To create queries manually instead of using the menus, click **Advanced mode**.

See [“Use Advanced mode to create a query for virtual machine selection”](#) on page 34.

Query builder reference for KVM virtual machines

You can use the Query builder to enter rules for the automatic selection of KVM virtual machines for backup.

Note: The advanced mode of the Query builder uses OData keywords and operators.

[Table 5-4](#) describes the fields and options for creating credential rules with the Query builder.

Table 5-4 Query builder options for KVM virtual machines

Query Builder fields	Description
and or	When you add two or more conditions, you can select a connector to join the rules.
Field	Select a parameter on which to build the rule. See Table 5-5 on page 32.
Operator	Select an operator. The available operators depend on the parameter that is selected for the Field . See Table 5-6 on page 32.
Value	Specifies a Value for the Field parameter. The Value field can be a list of possible values or a manual entry, depending on the selections that are made in the other fields. See the section called “Value” on page 33.

Field (keywords)

[Table 5-5](#) describes the keywords that are available in the **Field** dropdown. The values for each keyword (in the **Value** field) are case-sensitive.

Note: Use OData **Field** keywords are indicated for when you build queries for credential rules with the NetBackup APIs.

Table 5-5 Keywords in the **Field** list

Field keyword	OData field keyword	Description
description	description	The description of the virtual machine.
displayName	displayName	The virtual machine's display name.
kvmHostName	kvmHostName	The name of the KVM host.
powerState	powerState	The power state of the virtual machine.
title	title	The title from the metadata for the virtual machine.
uuid	uuid	The UUID of the virtual machine.
cluster	cluster	The OLVM cluster the virtual machine belongs to.
datacenter	datacenter	The OLVM datacenter the virtual machine belongs to.
host	host	The OLVM hypervisor host managing the virtual machine.
tagName	tagName	The name of the OLVM tag assigned to the virtual machine.

Operators

Table 5-6 describes the operators available in the **Operator** list. The table also indicates whether the values for each keyword (in the **Value** field) are case-sensitive.

Table 5-6 Operators in the **Operator** list

Operator	OData operator	Description
Contains	contains	Matches the value in the Value field wherever that value occurs in the string. Values are case-sensitive. For example: If the Value entry is 'dev', Contains matches strings such as '01dev', '01dev99', and 'devOP'. The name 'Development_machine' is not matched.
EndsWith	endswith	Matches the value in the Value field when it occurs at the end of a string. For example: If the Value entry is 'dev', Ends with matches the string '01dev' but not '01dev99', 'devOP', or 'development_machine'.

Table 5-6 Operators in the **Operator** list (continued)

Operator	OData operator	Description
Equal	equal	Matches only the value that is specified in the Value field. Values are case-sensitive. For example: If the display name to search for is 'VMtest27', Equal matches the virtual machine name VMtest27. The names VMTest27 or vmtest27 or vmTEST27 are not matched.
Greater	greater	Matches any value that is greater than the specified Value, according to the UTF-8 collating sequence.
GreaterEqual	greaterEqual	Matches any value that is greater than or equal to the value in the Value field, according to the UTF-8 collating sequence.
In	in	Matches any of the specified values in the Value field. For example: If the hosts in the Value field are 'kvm01','kvm02','kvm03', In matches any KVM host that has one of those names. If the names of your KVM hosts are not identical to any of the specified values, no match occurs. A host named KVM01A is not a match.
Less	less	Matches any value that is less than the specified Value, according to the UTF-8 collating sequence.
LessEqual	lessEqual	Matches any value that is less than or equal to the specified Value, according to the UTF-8 collating sequence.
NotEqual	ne	Matches any value that is not equal to the value in the Value field.
StartsWith	startswith	Matches the value in the Value field when it occurs at the start of a string. For example: If the Value entry is 'box', Starts with matches the string 'box_car' but not 'flatbox'.

Value

Table 5-7 describes the characters that can be entered in the **Value** field. The **Field** keyword determines case sensitivity.

Note: The character string you enter in the **Value** field must be enclosed in single quotes.

Table 5-7 Characters you can enter for Value

Character types	String characters allowed
Alphanumerics	A to Z, a to z, 0 to 9, - (minus sign), and special characters. Note: Decimal numbers only.
Wildcards	* (asterisk) matches everything. For example: **prod** matches the string 'prod' preceded or followed by any characters. ? (question mark) matches any single character. For example: 'prod??' matches the string 'prod' followed by any two characters.
Escape character.	\ (backslash) escapes the wildcard or meta-character that follows it. For example: To search for a string that contains an asterisk (such as test*), enter 'test\''
Quotation marks	Note: The characters you enter in Value must be enclosed in single quotes. To search for a string that contains quotation marks, escape each quote (\'). For example: To search for a string that includes single quotes (such as 'name'), enter "'name'"

Use Advanced mode to create a query for virtual machine selection

The Query builder's Advanced mode provides more flexibility in crafting rules for virtual machine selection, including the use of parentheses for grouping.

Note: In the NetBackup web UI, you must use OData keywords and OData operators in query rules:

See [“Query builder reference for KVM virtual machines”](#) on page 31.

To use Advanced mode to create a query for virtual machine selection

- 1 Create a KVM policy.
- 2 Select the **Backup selections** tab.
- 3 Locate **Query builder** and select **Advanced mode**.
- 4 You can use the Query builder menus to add query rules. You can also type in rules manually.

Here are some example queries:

```
startswith(displayName, 'vm3') and powerState eq 'Shut Off'  
  
contains(kvmHostName, 'hostab')
```

- 5 To insert a rule between existing rules, place the cursor where you want the new rule to start and type it in.
- When you create a rule with the drown-down menus, it appears at the end of the query. You can cut and paste it into the proper location.
- 6 To establish the proper order of evaluation in compound queries, use parentheses to group rules as needed. Compound queries contain two or more rules, joined by: and, and not, or, or not.

Example queries to select VMs for backup

This topic provides examples of the kinds of queries that you can create to automatically select KVM virtual machines for backup.

In the following example, the query selects KVM virtual machines with a host name that ends with the string `domain.com`. The query string with OData keywords and operators is: `endswith(kvmHostName), 'domain.com')`

Field	Operator	Value
kvmHostName	Ends with	domain.com

In the following example, the query selects a KVM virtual machine with the UUID `100faa79-1119-4c49-8f32-b4a165ee51d`. The query string with OData keywords and operators is: `uuid eq '100faa79-1119-4c49-8f32-b4a165ee51d6'`

Field	Operator	Value
uuid	Equal	100faa79-1119-4c49-8f32-b4a165ee51d6

Test a VM query

You can test a query that you create to preview the VMs for KVM that NetBackup discovers in the current NetBackup environment.

To test a VM query

- 1 Open the KVM policy.
- 2 Select the **Backup selections** tab.

3 Locate and select **Test query**.

The following information is displayed:

Query	The query criteria.
All	Displays the number of VMs in the NetBackup environment.
Included	Displays the number of VMs that match the query criteria.
Excluded	Displays the number of VMs that do not match the query criteria.
Failed	The virtual machine cannot be selected for backup because of a host name problem or other error. Also, the query cannot exclude the virtual machine. An explanation is included with the VM.
List of VMs	The names of the VMs in the NetBackup environment, based on the tab that you selected.

4 To perform an immediate discovery to update the asset information, scroll to the bottom of the **Test query** modal and select **Discover now**.

Note: NetBackup does not run discovery when the KVM policy runs. To reflect any new VMs in the policy, you must manually run discovery to discover those VMs.

5 Select **Close** when you are finished.

About the Reuse VM selection query results option

The Test query screen lists the virtual machines that NetBackup discovered in your KVM environment. Because the automatic selection feature is dynamic, later changes in the environment may affect which virtual machines match the query rules. For example: if virtual machines are added later, the current test results may not be identical to the virtual machines that are selected when the backup runs.

During the period you specify on **Reuse VM selection query results for**, NetBackup reuses the current list of virtual machines as the backup list. It does not consult the Query builder or rediscover virtual machines.

Note the following about the **Reuse VM selection query results** option:

- It determines how long the query results are reused.
- It has no effect on when the NetBackup policy schedule runs.

- The option is invalidated if the query rules are changed or if the policy attributes that affect discovery are changed. In that case, NetBackup rediscovers virtual machines the next time the policy runs.

For example: assume that the **Reuse VM selection query results for** option is set to 8 hours and your query selects turned-on virtual machines. If additional virtual machines are turned on during the 8-hour period, they are not added to the policy's backup list. The policy backs up the virtual machines that were last added to the list (such as when the policy was created). After 8 hours, when the policy runs next, the recently turned-on virtual machines are discovered and added to the backup list.

Assume that the next backup occurs before the **Reuse** period expires and a virtual machine was renamed during the Reuse period. Then NetBackup backs up the renamed virtual machine under its original name. Because the reuse period has not expired, NetBackup does not rediscovers virtual machines and therefore cannot identify the virtual machine by its new name. (NetBackup identifies the virtual machine by its instance UUID.) To have backed up the virtual machine with its new name, the **Reuse** period should have been set to a shorter interval and the discovery process should have been initiated.

Note: The virtual machines that are selected for backup are not displayed on the policy **Backup selections** tab. To see which virtual machines NetBackup has selected and backed up, refer to the following topic.

See [“Test a VM query”](#) on page 35.

Backup options on the KVM attributes tab

The **KVM** tab displays when you select KVM as the policy type.

The following topics describe the KVM backup options.

See [“Optimizations options \(KVM\)”](#) on page 38.

See [“Primary VM identifier options \(KVM\)”](#) on page 39.

See [“Existing snapshot handling options \(KVM\)”](#) on page 41.

See [“KVM - Advanced attributes”](#) on page 42.

KVM Backup Host

The KVM backup host is a NetBackup media server or client that performs backups on behalf of the virtual machines.

Table 5-8

Option	Description
KVM Backup Host	The name of the NetBackup backup host which communicates with the OLVM server. Only used for backups of OLVM VMs. For a list of supported platforms for the backup host, see the <i>NetBackup Software Compatibility List</i>.

Optimizations options (KVM)

The following options set the type and scope of the KVM virtual machine backup.

Table 5-9 Optimizations

Option	Description
Enable file recovery from VM backup	This option allows restore of individual files from the backup. With or without this option, you can restore the entire virtual machine. To perform a KVM backup to a deduplication storage unit, select this option. This option provides the best deduplication rates. To back up a virtual machine that contains Arctera InfoScale volumes, disable this option. Also make sure that the Exclude deleted blocks option is disabled. Note: For a Linux virtual machine, the name of an LVM volume can include any of the following special characters: . (period), _ (underscore), - (hyphen). No other special characters are supported. If other special characters are in the volume name, the Enable file recovery from VM backup option does not work. As a result, you cannot restore individual files from that volume.
Enable block-level incremental backup	For block-level backups of the virtual machine. This option reduces the size of the backup image.
Exclude deleted blocks	Reduces the size of the backup image by excluding any unused or deleted blocks within the file system on the virtual machine. This option supports the following file systems: Windows NTFS, and Linux ext2, ext3, ext4, and XFS. This option uses proprietary mapping technology to identify vacant sectors (allocated but empty) within the file system. To back up a virtual machine that contains Arctera InfoScale volumes, disable this option. Also make sure that the Enable file recovery from VM backup option is disabled.

Table 5-9 Optimizations (*continued*)

Option	Description
Exclude swap and paging files	Reduces the size of the backup image by excluding the data in the guest OS system paging file (Windows) or the swap file (Linux). Note: This option does not exclude the swapping and paging files from the backup: it only excludes the data in those files. If the files are restored, they are restored as empty files. Note: For a Linux virtual machine, this option disables the swap file when you restore the virtual machine. You must reconfigure the swap file after the virtual machine is restored. To allow the virtual machine to be restored with its swap file enabled, do not select Exclude swap and paging files.

Primary VM identifier options (KVM)

This setting specifies the type of name by which NetBackup recognizes virtual machines when it selects them for backup.

The name you use for the **Primary VM identifier** may have restrictions.

See [“NetBackup character restrictions for the Primary VM identifier”](#) on page 39.

Table 5-10 Primary VM identifier

Option	Description
VM display name	The name of a virtual machine in a KVM environment. When the virtual machines are included in a NetBackup policy, restrictions apply to the characters that are allowed in the virtual machine display name. See “NetBackup character restrictions for the Primary VM identifier” on page 39.
VM UUID	The globally unique ID that is assigned to the virtual machine when the virtual machine is created. This ID uniquely identifies the virtual machine on a KVM host or OLVM server.

NetBackup character restrictions for the Primary VM identifier

For virtual machines in a NetBackup policy, certain characters are not allowed in their names. The backup policy **Primary VM identifier** field identifies the name type that NetBackup uses to select VMs.

See [“Primary VM identifier options \(KVM\)”](#) on page 39.

If the name contains disallowed characters, backups or restores may fail.

The following table describes the characters and strings that NetBackup does not allow for backup or restore in the **Primary VM identifier**, except where noted.

Table 5-11 Disallowed characters and strings in the Primary VM identifier

Character/string	Description	Notes
"	Quotation mark, Unicode x22.	
\$	Dollar sign, Unicode x24.	
'	Apostrophe, Unicode x27.	
*	Asterisk, Unicode x2A.	
,	Comma, Unicode x2C.	
:	Colon, Unicode x3A.	
;	Semi-colon, Unicode x3B.	
?	Question mark, Unicode x3F.	
@	At sign, Unicode x40.	
	Vertical line, Unicode x7C.	
`	Grave accent, Unicode x60.	
´	Acute accent, Unicode xB4.	
%	Percent sign, Unicode x25.	In an intelligent policy query and VM search results, NetBackup converts % in the display name of Included VMs to the literal string %25 . When you specify a display name in a query, replace the % character with %25 .
&	Ampersand sign, Unicode x26.	
<	Less than sign, Unicode x3C.	
>	Greater than sign, Unicode x3E.	
-	Hyphen-minus, Unicode x2D.	Disallowed in the first position only.
/	Solidus, Unicode x2F.	Disallowed in the VM display name; allowed in other objects.
\	Reverse solidus, Unicode x5C.	Disallowed in the VM display name; allowed in other objects.

Table 5-11 Disallowed characters and strings in the Primary VM identifier
(continued)

Character/string	Description	Notes
.	Full stop (period), Unicode x2E.	Disallowed in the VM display name when in the last position; allowed in other objects.
□	Space, Unicode x20.	In an intelligent policy query and VM search results, NetBackup converts a space character in the display name of Included VMs to the literal string %20 . When you specify a display name in a query, replace the space character with %20 .
Unicode characters greater than x7F (non-ASCII)		Disallowed when the backup policy specifies the VM display name as the primary VM identifier.
%2f	Literal string, not a Unicode character definition.	Disallowed in the VM display name; allowed in other objects.
%5c	Literal string, not a Unicode character definition.	Disallowed in the VM display name; allowed in other objects.

Additional character restrictions for VM names can be found in the *NetBackup Cloud Administrator's Guide*, available from this location:

<https://support.cohesity.com/s/article/article-100040135>

Existing snapshot handling options (KVM)

Undeleted snapshots can contribute to disk space and performance issues. NetBackup offers the following options to clean up snapshots as part of the backup process.

Table 5-12 Existing snapshot handling: Options

Option	Description
Remove NetBackup snapshots and continue the backup	If a virtual machine snapshot exists that a NetBackup backup previously created: NetBackup removes the old snapshot, creates an updated snapshot, and proceeds with the virtual machine backup.

Table 5-12 Existing snapshot handling: Options (*continued*)

Option	Description
Continue the backup	NetBackup ignores any existing virtual machine snapshots (including snapshots previously created by NetBackup) and proceeds with snapshot creation and the backup.
Stop the backup if any snapshots exist	If any snapshot exists on the virtual machine, NetBackup stops the job for that virtual machine only.
Stop the backup if NetBackup snapshots exist	If a virtual machine snapshot exists that a NetBackup backup previously created, NetBackup stops the job for that virtual machine only.

KVM - Advanced attributes

The following additional parameters are available for KVM backups. In most situations, the best settings are the defaults.

Table 5-13 KVM advanced attributes

Configuration parameter	Description
Virtual machine quiesce	This option is enabled by default. In the great majority of cases, you should accept the default. I/O on the virtual machine is quiesced before NetBackup creates the snapshot. Without quiescing file activity, data consistency in the snapshot cannot be guaranteed. If not consistent, the backed-up data may be of little or no value. If this option is disabled, the snapshot is created without quiescing I/O on the virtual machine. In this case, you must perform your own analysis for data consistency in the backup data. Caution: Cohesity does not recommend that you disable quiesce. In most cases, this option should be enabled. Note: If the QEMU guest agent is not installed, the backup fails. Perform snapshot without quiescing if quiesced snapshots fail Select this option to automatically perform the snapshot with quiescing if any backups of quiesced snapshots fail.

View the protection status of KVM virtual machines

You can view the protection status for the policies that are used to protect VMs on KVM hosts.

To view the protection status KVM virtual machines

- 1 On the left, select **Workloads > KVM**.
- 2 Select the **Virtual machines** tab.

The **Last successful backup** column indicates the date and time of the last successful backup. The **Protected by policy** column indicates the name of the policy that protects the virtual machine.

Perform a manual backup

After you configure the servers and assets in your environment, you can test the configuration settings with a manual backup. Perform a manual backup (or backups) from a policy with the automatic backup schedules that you created.

To perform a manual backup from a policy

- 1 On the left, select **Protection > Policies**.
- 2 Select the policy you want to test.
- 3 Select **Manual backup**.
- 4 Select the schedule that you want to use for the manual backup.
- 5 Select the clients that you want to include for the manual backup.

Recovering KVM virtual machines

This chapter includes the following topics:

- [Considerations and limitations for KVM recovery](#)
- [About the pre-recovery check](#)
- [Recover a KVM virtual machine](#)
- [Download files and folders](#)
- [Single-file restore \(SFR\) to a NetBackup client](#)
- [Restore OLVM Virtual Machines](#)
- [Restore files from OLVM VM backups \(Single file restore\)](#)

Considerations and limitations for KVM recovery

Before you perform KVM recovery, review the following considerations and limitations:

- You can only recover to a storage pool that NetBackup has discovered. If no storage pools have been discovered, you must first create a storage pool and then run discovery to discover that storage pool.
- Full VM recovery is supported with both full and incremental backups.
- If a VM disk did not reside in a storage pool at time of backup, the recovery option **Restore to the original location** is not available.
- NetBackup supports backup of Linux FIFO files on KVM guests. However, NetBackup does not support restoring FIFO files individually through KVM Single

File Restore (SFR). FIFO files are restored when you recover the entire virtual machine.

A granular or KVM SFR job may fail or may not create the named pipe on the destination. For example, destination `nbtar` reports status 185. The `tar` did not find all the files to be restored, or the restore completes without the FIFO being present, even though the object appears in browse/selection.

SFR builds a `tar` stream. FIFOs are special files and the path from Catalog > stream > `nbtar` can omit or mishandle the FIFO. This is a known limitation and not a supported granular use case for FIFOs.

To resolve the issue, FIFO files should be restored when KVM full VM recovery is performed.

- Downloading of files and folders with SFR is not supported for accelerator-disabled incremental backup images.
- Raw disks are not mapped for file boundaries and are not supported with SFR.

About the pre-recovery check

The pre-recovery check verifies the following:

- Use of supported characters and the character length of the display name.
- Existence of a VM with the same display name or UUID.
- Connectivity with the KVM host.
- Available space on the destination volume.

Recover a KVM virtual machine

You can recover a VM to its original location where it existed when it was backed up or to different location. You can choose to recover from the default copy of the backup image or from an alternate copy, if one exists. The default copy is also known as the primary copy.

To recover a KVM virtual machine

- 1 On the left, select **Workloads > KVM**.
- 2 Select the **Virtual machines** tab.
- 3 Locate and select the VM. Then select **Recover**.

- 4 Select the **Recovery points** tab. In the calendar view on the left, select the date on which the backup occurred.

The available images are listed in rows with the backup timestamp for each image.
- 5 For the image that you want to recover, select one of the following image recovery options:
 - **Recover**
Recover from the default copy of the backup image. This option is displayed if only one copy exists.
 - **Recover from default copy**
Recover from the default copy of the backup image. This option is displayed if more than one copy exists.
 - **nn copies**
Recover from the default copy or a different copy of the backup image. NetBackup allows up to ten copies of the same backup image. All available copies are displayed when you select this option. For each copy, the **Storage** name, **Storage server**, and the **Storage server type** are displayed.
- 6 Select **Restore virtual machine** for the copy that you want to recover.
- 7 In the **Recovery target** step, do the following:
 - Review the **Restore to** values.
The default values are populated from the backup image of the VM.
 - If you want to apply a different display name, enter that name.
 - For KVM hosts, to recover to a different KVM host, search for that host name.
 - For OLVM servers, to recover to a different cluster, select the cluster field and browse/search for the cluster.
 - To recover to alternate storage, select **Restore to alternate storage**.
For each disk, select the **Destination storage pool** and enter the **Destination volume** to which you want to recover.
- 8 Select **Next**.

9 Review the restore options.

Allow overwrite of existing virtual machine	NetBackup deletes any VM with the same display name or UUID that exists at the destination, before the recovery starts. Note that, NetBackup deletes any VM with the same display name or UUID, it may not be the same VM, but another VM having the same display name or UUID.
Power on after recovery	Automatically turns on the VM when the recovery is complete.
Create a new VM UUID	Restores the VM with a new VM UUID instead of the original VM UUID.

10 Select **Next**.

11 NetBackup performs the pre-recovery checks.

12 Resolve any errors.

You can choose to ignore the errors. However, the recovery may fail.

13 Select **Start recovery**.

Select the **Restore activity** tab to monitor a job's progress. Select a specific job to view its details.

Download files and folders

To recover files and folders

- 1 On the left, select **Workloads > KVM**.
- 2 Select a VM and then select the **Recovery points** tab.
- 3 Click **Recover > Download files and folders**.
- 4 Click **Add**.
- 5 On the **Add files and folders** page, select files or folders that you want to recover and click **Add**.
- 6 Click **Next**.
- 7 During the **Create download package** step, click the **Download** icon when the download package is ready.

Single-file restore (SFR) to a NetBackup client

You can perform single file restore to a NetBackup client.

Single-file restore to a NetBackup client

- 1 On the left select **Recovery**. In the **Regular recovery** box, click **Start recovery**
- 2 During the **Basic properties** step, select the policy type as **KVM** and the restore type as normal backups.
- 3 During the **Basic properties** step, click **Select client** next to the **Source client** field to choose the source client.

This is the VM that was backed up, which contains files and folders that you browse to recover.

- 4 In the **Select source client** dialog box, choose a source client and click **Apply**.
- 5 During the **Basic properties** step, select the client next to the **Destination client** field. This is a NetBackup primary, media, or client where the files or folders will be restored to.
- 6 In the **Select destination client** screen, choose a destination client.
- 7 Click **Apply**.
- 8 During the **Basic properties** step, click **Next**.
- 9 During the **Recovery details** step, click **Edit** to select the backup image and browse for files/folders.

Alternatively, click **Most recent** or **All** backups to select the backup image to browse files/folders from.

By default, files/folders from the most recent backup image will be displayed.

- 10 On the **Edit date** range screen, select the **Use date picker** or **Use backup history** radio button to choose which backup image to browse files/folders from. Click **Apply**.
- 11 During the **Recovery details** step, select files/folders to restore.
Click **Next**.
- 12 During the **Recovery options** step, select the **Restore target** and **Recovery** options and the media server.
Click **Next**.
- 13 During the **Review** step, review the information and click **Start recovery**.

Restore OLVM Virtual Machines

You can restore a full OLVM VM from a NetBackup backup image. NetBackup creates the restored VM in OLVM with all original properties. No manual post-restore steps are required.

A full VM restore recreates the following VM properties from the backup catalog:

- Display name and UUID (UUID preservation is optional)
- CPU topology
- All VM disks are recreated and attached with the original disk interface, disk format, provisioning, and storage domain mapping
- NIC configuration - Network interfaces are recreated with the original network assignments.
- BIOS and firmware type
- High-availability configuration (enabled state and priority)
- VM tags
- Boot order
- Delete protection setting
- Memory policy (guaranteed and maximum memory)

To restore OLVM VMs

- 1 In the NetBackup Web UI, navigate to **Workloads > KVM**.
- 2 Search for the VM by name or browse the VM inventory, then select the OLVM VM asset.
- 3 Select a backup image (recovery point), click **Recover**, and choose **Restore virtual machine**.
- 4 On the **Recovery target** page, select the restore destination:
 - Original location - restores the VM to the same OLVM cluster and storage domains it was backed up from.
 - Alternate location - select a different OLVM cluster or storage domains.
- 5 (Optional) You can change the restored VM name to avoid naming conflicts with the original VM.
- 6 Go to the **Recovery options** page to configure the overwrite, power on, and new UUID options.
- 7 If the pre-recovery check passes, click **Restore**. NetBackup creates the VM in OLVM, writes all disk data, and applies the original VM properties.

Restore files from OLVM VM backups (Single file restore)

You can restore individual files from an OLVM VM backup without restoring the entire VM. Two methods are available.

Method 1: Restore to a NetBackup Client inside the guest VM

This method requires the NetBackup client to be installed inside the guest VM (not on the hypervisor host).

1. In the NetBackup Web UI, navigate to **Recovery** and click **Start recovery**.
2. Select the **Policy type** as **KVM**.
3. Select the **Source client** and **Destination client**.
4. Select a target directory.
5. Click **Restore**. The files are transferred to the specified NetBackup client to the selected location.

Method 2: Download Files from the NetBackup Web UI

This method does not require an agent in the guest VM. Files are downloaded directly through the NetBackup Web UI.

1. In the NetBackup Web UI, navigate to **Workloads > KVM**. This option is not available from **Recovery**.
2. Select the OLVM VM asset, then select a backup image (recovery point).
3. Click **Recover** and choose **Download files and folders**.
4. Browse the file system of the backup image and select the files to download.
5. Click **Download**.
6. The selected files are downloaded to your browser download location.

Troubleshooting KVM backups and recovery

This chapter includes the following topics:

- [NetBackup logging for KVM](#)
- [Configuring VxMS logging](#)
- [Troubleshooting a KVM discovery or a validate operation](#)
- [Using a custom overlay path location](#)
- [Troubleshooting OLVM backup and restore](#)
- [OLVM Backup Performance Tuning \(bp.conf\)](#)

NetBackup logging for KVM

For log messages about KVM backups or KVM restores, see the following NetBackup log directories.

Table 7-1

Log directory	Contains the messages on	Resides on
<i>install_path</i> \NetBackup\logs\bpbrm	Backup and restore	Primary or media server
<i>install_path</i> \NetBackup\logs\bpptm	Backup and restore	Media server
<i>install_path</i> \NetBackup\logs\bpfis	Snapshot creation and backup	KVM host/Backup host
<i>install_path</i> \NetBackup\logs\bpccd	Snapshot creation and backup	KVM host/Backup host
<i>install_path</i> \NetBackup\logs\bpbkar	Backup	KVM host/Backup host

Table 7-1 (continued)

Log directory	Contains the messages on	Resides on
<i>install_path</i> \NetBackup\logs\lbprd	Restore	Primary server
<i>install_path</i> \NetBackup\logs\bpVMutil	KVM host configuration, discovery, and restores	KVM host/Backup host
<i>install_path</i> \NetBackup\logs\nbproxy	Policy configuration	KVM host/Backup host
<i>install_path</i> \NetBackup\logs\ncfnbcs (originator ID 366) ncfnbcs uses unified logging. See the NetBackup Logging Reference Guide for information on how to use unified logs.	Automatic virtual machine selection and KVM host configuration and discovery	Primary server, KVM host/Backup host
<i>install_path</i> \NetBackup\logs\ncfnbrestore (originator ID 357) ncfnbrestore uses unified logging. See the <i>NetBackup Logging Reference Guide</i> for information on how to use unified logs.	Restore	Primary/KVM host
Windows: <i>install_path</i> \NetBackup\logs\vxms Linux: /usr/openv/netbackup/logs/vxms	File mapping during backup	KVM host/Backup host See "Configuring VxMS logging" on page 53. Note: The use of VxMS logging can reduce the performance of the backup host.
<i>install_path</i> \NetBackup\logs\nbweb service	KVM host configuration and discovery	Primary server

Note: Except for unified logging directories, these log directories must already exist in order for logging to occur. If these directories do not exist, create them.

To create most of these log directories, run the following command on the NetBackup servers and KVM hosts:

Windows:*install_path*\NetBackup\logs\mklogdir.bat

UNIX (on primary or media servers):/opt/openv/netbackup/logs/mklogdir

See ["Configuring VxMS logging"](#) on page 53..

More detail is available on snapshot logs and logging levels. See the [NetBackup NAS Administrator's Guide](#). A broader discussion of logging is available. See the [NetBackup Logging Reference Guide](#).

Configuring VxMS logging

The following procedures describe how to configure VxMS logging for NetBackup.

VxMS logging on a Linux backup host

To configure VxMS logging on a Linux backup host

- 1 Create the VxMS log directory:

```
/usr/opensv/netbackup/logs/vxms
```

Note: For logging to occur, the VxMS directory must exist.

Note: If you have run the NetBackup `mklogdir` command, the VxMS log directory already exists.

- 2 Add the following to the `/usr/opensv/netbackup/bp.conf` file:

```
VXMS_VERBOSE=<numeric value of 0 or greater>
```

See [Table 7-2](#) for the available logging levels.

- 3 To change the log location, enter the following in the `bp.conf` file:

```
vxmslogdir=path to new log location
```

Note: If the VxMS log location is changed, the Logging Assistant does not collect the logs.

VxMS logging on a Windows backup host

To configure VxMS logging on a Windows backup host

- 1 Create the VxMS log directory:

```
install_path\NetBackup\logs\vxms
```

Note: For logging to occur, the VxMS folder must exist.

Note: If you have run the NetBackup `mklogdir.bat` command, the VxMS log directory already exists.

- 2 In the Windows registry, create the DWORD registry entry `VXMS_VERBOSE` in the following location:

HKEY_LOCAL_MACHINE > SOFTWARE > Veritas > NetBackup > CurrentVersion > Config

- 3 To configure the logging level, set the numeric value of `VXMS_VERBOSE` to 0 or greater. Larger numbers result in more verbose logs.

See [Table 7-2](#) for the available logging levels.

- 4 To change the log location:

- Open regedit and go to the following location:
HKEY_LOCAL_MACHINE > SOFTWARE > Veritas > NetBackup > CurrentVersion
- Create the registry entry `vxmslogdir` with a string value (`REG_SZ`). For the string value, specify the full path to an existing folder.

Note: You can use NTFS compression on VxMS log folders to compress the log size. The new logs are written in compressed form only.

Note: If the VxMS log location is changed, the Logging Assistant does not collect the logs.

VxMS logging levels

[Table 7-2](#) lists the VxMS logging levels.

Note: Logging levels higher than 5 cannot be set in the Logging Assistant.

Note: Logging levels higher than 5 should be used in very unusual cases only. At that level, the log files and metadata dumps may place significant demands on disk space and host performance.

Table 7-2 VxMS logging levels

Level	Description
0	No logging.
1	Error logging.
2	Level 1 + warning messages.
3	Level 2 + informative messages.
4	Same as level 3.
5	Highly verbose (includes level 1) + auxiliary evidence files (<code>.mmf</code> , <code>.dump</code> , <code>VDDK logs</code> , <code>.xml</code> , <code>.rvpmem</code>). You can set the logging level for the VDDK messages.

Table 7-2 VxMS logging levels (*continued*)

Level	Description
6	VIX (VMware virtual machine metadata) dumps only.
7	VHD (Hyper-V virtual machine metadata) dumps only.
> 7	Full verbose + level 5 + level 6 + level 7.

Troubleshooting a KVM discovery or a validate operation

Discovery or Validate operation fails for the KVM host

Recommended action: Ensure sure that the KVM host is reachable and that NetBackup services are up.

A backup of a virtual machine without a storage pool cannot be restored to the original location

If the virtual machine disk files did not reside on the storage pool during the backup, the pre-recovery check fails if the user attempts to restore to the original location. In this case, restore to an alternate location. By default for this kind of restore, the **Destination storage pool** and the **Destination volume** values are empty for the virtual machine. Select the wanted values before you continue with the restore.

A backup job fails with error 4726 - Failed to create snapshot of the specified VM.

The bpbmr logs on the media server contain the following message:

```
12:41:49.943 [3275984.3275984] <2> get_bpfis_msg: bpfis buff: FTL - Unable to
quiesce VM filesystem.
Verify the QEMU guest agent is installed and running.
12:41:49.943 [3275984.3275984] <32> get_bpfis_msg: from client alpine2: FTL - Unable
to quiesce VM filesystem.
Verify the QEMU guest agent is installed and running.
12:41:49.944 [3275984.3275984] <2> set_job_details: Tfile (12): LOG 1752774109 32
bpbmr 3275984 from client
alpine2: FTL - Unable to quiesce VM filesystem. Verify the QEMU guest agent is
installed and running.
12:41:49.944 [3275984.3275984] <2> send_job_file: job ID 12, ftype = 3 msg len = 146,
msg = LOG 1752774109 32
```

bpbrm 3275984 from client alpine2: FTL - Unable to quiesce VM filesystem. Verify the QEMU guest agent is installed and running.

This error can occur if the **Virtual machine quiesce** option is selected without the option **Perform snapshot without quiescing if quiesced snapshots fail** for the backup policy.

A snapshot may fail if the virtual machine can't be quiesced. This error usually means that the QEMU agent isn't installed or isn't running on the guest system. To fix this issue, you can either resolve the QEMU agent issue on the guest VM to allow for a successful quiesce operation. Or, select the option **Perform snapshot without quiescing if quiesced snapshots fail** option.

A backup of a virtual machine fails if the QEMU guest agent is not installed

The KVM advanced attribute **Virtual machine quiesce** is enabled by default and requires that the QEMU guest agent is installed. If not, the backup fails.

Using a custom overlay path location

Snapshots of block device disk types require an explicit overlay file. By default, these are created in the `/var/libvirt/images` directory on the KVM host.

To use a custom overlay path location, set the `KVM_OVERLAY_PATH` configuration option (`bp.conf` file on UNIX or Windows registry) on the KVM host using the `nbsetconfig` command.

Troubleshooting OLVM backup and restore

Previous checkpoint deleted outside NetBackup

If an oVirt checkpoint recorded in the NBU catalog is deleted or missing on the OLVM engine (orphaned / reset / manual virsh / oVirt admin action), the next scheduled incremental will automatically fall back to a full backup to avoid a chain gap.

Do not manually delete oVirt checkpoints for backed-up VMs outside NetBackup. NetBackup will manage the checkpoint chain.

Recovering from an Interrupted OLVM backup

If a previous OLVM backup was interrupted, some backup activity may still be active on the OLVM engine when the next job starts. This can cause conflicts, but NetBackup detects and resolves them automatically.

NetBackup handles these situations as follows:

- If a data transfer from a previous backup is still in progress, NetBackup reuses it instead of starting a duplicate.
- Before completing a backup, NetBackup clears any leftover transfers so that finalizing the backup does not fail.
- When a new job starts, NetBackup completes any backups that were left unfinished by earlier runs, while preserving incremental (checkpoint) progress so that data does not need to be re-transferred.

Recommended action: If the engine still holds a stale backup, manually finalize the backup on the engine, then re-run the job.

Async transfer failure

If the async pipeline cannot start (thread creation/resource issue), OLVM transparently falls back to synchronous ImageIO I/O. Mid-transfer retry exhaustion aborts the disk and returns a retryable job error.

Recommended action: Re-run the job. Tune the `OLVM_ASYNC_* bp.conf` keys.

Overwriting existing virtual machines

When you enable the **Overwrite the existing virtual machine** option during a full VM recovery, NetBackup checks for and removes conflicting VMs before restoring, based on two criteria:

- Matching display name and datacenter:
If a VM with the same display name already exists in the same datacenter, NetBackup overwrites it. VMs with the same name in other datacenters are not affected.
- Matching UUID
If you also choose to restore the VM with its original UUID, and a VM with that same UUID already exists on the OLVM server, NetBackup removes the existing VM so the recovered VM can retain its original UUID.

If the **Overwrite the existing virtual machine** option is disabled, NetBackup does not delete any existing VM, and the recovery fails if a conflicting VM is found.

KVM backup hosts

To configure a KVM backup host, add a `KVM_PROXY_SERVER` entry in `bp.conf/registry` on the primary server for each NetBackup client you want to use.

For example:

```
KVM_PROXY_SERVER = nbclient1.com
KVM_PROXY_SERVER = nbclient2.com
```

After this configuration is completed, NetBackup clients become available for selection as backup hosts in KVM policies.

OLVM backup may automatically enable the Enable Incremental Backup setting on VM disks

NetBackup incremental backups of OLVM virtual machines may automatically enable the **Enable Incremental Backup** setting on VM disks, overriding an administrator's decision to leave the setting disabled in the OLVM/oVirt UI.

Recommended action: If you require **Enable Incremental Backup** to remain disabled for a disk, manually clear the checkbox in the OLVM/oVirt admin UI. Navigate to **Compute > Virtual Machines > <virtual machine> > Disks > Edit > disk**, clear the **Enable Incremental Backup** checkbox after each backup completes.

OLVM Backup Performance Tuning (bp.conf)

NetBackup transfers OLVM disk data using an asynchronous, pipelined mechanism. You can tune the transfer behavior by adding the following keys to the `bp.conf` file on the backup host. Changes take effect on the next backup job. No service restart is required.

Table 7-3

bp.conf Key	Default Value	Description
OLVM_ASYNC_TRANSFER_ENABLED	1	Enables (1) or disables (0) the asynchronous pipelined disk transfer. When disabled, NetBackup falls back to synchronous I/O. NetBackup also falls back automatically if the async pipeline fails to initialize.
OLVM_ASYNC_READ_THREADS	16	Number of parallel read threads used during backup. Increase for high-throughput storage; decrease if the Backup Host or OLVM engine is resource-constrained.
OLVM_ASYNC_WRITE_THREADS	8	Number of parallel write threads used during restore. Adjust in proportion to OLVM_ASYNC_READ_THREADS if changing restore performance.

Table 7-3 (continued)

bp.conf Key	Default Value	Description
OLVM_ASYNC_BUFFER_SIZE_MB	16	Size of each transfer buffer, in megabytes. Shared between backup and restore pipelines. Larger buffers can improve throughput on high-latency networks. Smaller buffers reduce memory usage.
OLVM_ASYNC_BUFFER_COUNT	16	Number of buffers in the pool per job. Shared between backup and restore pipelines. The working set per job is approximately $\text{OLVM_ASYNC_BUFFER_SIZE_MB} \times \text{OLVM_ASYNC_BUFFER_COUNT}$ (default: 256 MB).
OVIRT_IMAGEIO_INACTIVITY_TIMEOUT	172800 (48 hours)	Timeout, in seconds, for inactive OLVM image transfer sessions. Increase on slow or high-latency networks to prevent premature session termination.
OLVM_ASYNC_RETRY_COUNT	3	Number of retry attempts per chunk before the async transfer marks the chunk as failed and triggers a job error. Set to 0 to disable retries.
VIRTUALIZATION_HOSTS_SECURE_CONNECT_ENABLED	(secure)	Set to No to disable TLS certificate verification.

Note: The buffer size (OLVM_ASYNC_BUFFER_SIZE_MB) and buffer count (OLVM_ASYNC_BUFFER_COUNT) are shared between the backup and restore pipelines. Changing these values affects both operations. The thread counts (OLVM_ASYNC_READ_THREADS, OLVM_ASYNC_WRITE_THREADS) are independent for backup and restore.